

SimpleSight™ Wireless 5" LED Single Screen Monitor **RVS-15WM**

**REAR VIEW
SAFETY**
A Safe Fleet Brand



Perfection takes time, especially with something as complicated as wireless transmission. Our newest wireless monitor, part of our new SimpleSight™ Series was born from years of testing and multiple prototypes. This monitor can receive a 100' digital wireless signal which is guaranteed to work even at highway speeds. Users can pair this wireless monitor with our compatible wireless camera (**RVS-55**) without leaving the cab via Instant Pair technology.

Specifications

PANEL SIZE	5" LED DIGITAL PANEL	OPERATING TEMP.	-20°C ~ +70°C RH 90% MAX
VIDEO SYSTEM	NTSC / PAL AUTO DETECTION	STORING TEMP.	-30°C ~ +80°C RH 90% MAX
RESOLUTION	480 X 3 (RGB) X 272	FREQUENCY	2400 - 2500 MHZ
BRIGHTNESS	450 CD/m ²	TRANSMISSION TYPE	DIGITAL WIRELESS
CONTRAST RATIO	500:1	TRANSMISSION RANGE	100 FT
SCREEN MODE	16:9	VIDEO INPUT	1 CHANNEL
FIELD OF VIEW	TOP 50°, BOTTOM 70°, L/R 70°	VIDEO SOURCE	1VP-P 75Ω
AUDIO OUTPUT	OPTIONAL; 0.5W SPEAKER	AUTO PAIR	YES
DOT PITCH	0.077 (W) × 0.231(H) MM	POWER CONSUMPTION	ABOUT 4W
ACTIVE AREA	110.000 (W) × 62.832 (H) MM	OVERALL DIMENSIONS	5.25" (H) X 7" (L) X 1.5" (D)
POWER INPUT	DC10 - 32V		
POWER SUPPLY	DC9-32V		