

G - SERIES BACKUP CAMERA SYSTEM WITH AUTO DIMMING AND ONSTAR RVS - 776718 - DOS

**REAR VIEW
SAFETY**
A Safe Fleet Brand



 **AUTO-DIMMING**

 **ON-STAR**

For a backup camera system which fits almost any vehicle and is virtually invisible, look no further than the G-Series Camera System. This system features the legendary G-Series Monitor and the 776 Camera which despite its small size is powerfully built to withstand all weather conditions.

In addition to providing a display for your backup camera this mirror monitor also comes with auto-dimming and OnStar. This means that together with it's reflective abilities, it also dims reflected headlights automatically to reduce distraction to the driver. With built-in OnStar, all OnStar features and benefits are available with this monitor with just a push of a button.

The backup camera is completely waterproof with an IP68 rating and boasts excellent night vision. The system comes included with all parts necessary for installation and a one year warranty.

G - SERIES BACKUP CAMERA SYSTEM WITH AUTO DIMMING AND ONSTAR

RVS - 776718 - DOS



- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- BUILT-IN ONSTAR, ALL ONSTAR FEATURES AND BENEFITS ARE AVAILABLE WITH JUST A PUSH OF A BUTTON
- SUPER BRIGHT 4.3" COLOR TFT DIGITAL DISPLAY
- REPLACING THE EXISTING REAR VIEW MIRROR, THE BRIGHT SCREEN AND REFLECTIVE ABILITY CONTRIBUTE TO AN ALL-IN-ONE BACKUP EXPERIENCE
- NIGHT VISION PROVIDES A GREAT PICTURE AT NIGHT USING VERY LITTLE AMBIANT LIGHT



MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
TYPE	TFT LCD
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20°C ~ +75°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	10.43" (L) X 3.46" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX