

# G - SERIES BACKUP CAMERA SYSTEM WITH BLUETOOTH

RVS - 776718 - BT

REAR VIEW  
**SAFETY**  
A Safe Fleet Brand

 **BLUETOOTH**



For a backup camera system which fits almost any vehicle and is virtually invisible, look no further than the G-Series Camera System. This system features the legendary G-Series Monitor and the 776 Camera which despite its small size is powerfully built to withstand all weather conditions.

Our Bluetooth Mirror Monitor displays the backup camera and provides hands free control to your mobile phone. Its Bluetooth function allows it to connect to your smartphone and gives you the control to make and answer calls directly through the mirror! Music can also be played through this connection and the phone's voice recognition can be accessed by pressing the microphone button on the monitor allowing you to make a call, play music or get directions, by simply saying so!

Camera is completely waterproof with an IP68 rating and boasts excellent night vision. The system comes included with all parts necessary for installation and a one year warranty.

# G - SERIES BACKUP CAMERA SYSTEM WITH BLUETOOTH RVS - 776718 - BT

**REAR VIEW  
SAFETY**  
A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- BLUETOOTH MIRROR MONITOR ALLOWING YOU TO MAKE A CALL, PLAY MUSIC OR GET DIRECTIONS, SIMPLY WITH YOUR VOICE
- SUPER BRIGHT 4.3" COLOR TFT DIGITAL DISPLAY
- MIRROR MOUNTED MONITOR ATTACHES TO WINDSHIELD, REPLACING EXISTING REAR VIEW MIRROR
- NIGHT VISION PROVIDES A GREAT PICTURE AT NIGHT USING VERY LITTLE AMBIANT LIGHT



## MONITOR

TYPE	TFT LCD
SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

## CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP-P, 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX