

# BACKUP CAMERA SYSTEM WITH QUAD VIEW MONITOR (KOREAN) RVS - 1213

REAR VIEW  
**SAFETY**  
REVERSE WITH CONFIDENCE™



This four channel, quad view, industrial grade, completely weatherproof backup camera system is complete with a crystal clear 7" DIGITAL TFT LCD Quad View Color Monitor which boasts an IP65 weatherproof rating. The monitor also includes mirror image capability, a surface mount bracket and automatic system switch. The system boasts a large 130° viewing angle, a SONY CCD sensor backup camera with 30 foot infra-red night vision and all the wires, connectors and mounts you will need. The rear view camera is completely weatherproof with an IP68 rating, strong and reliable, shock resistant with a 100G impact rating (highest in the industry). The system comes with a one year warranty.



# BACKUP CAMERA SYSTEM WITH QUAD VIEW MONITOR (KOREAN) RVS - 1213

REAR VIEW  
**SAFETY**  
REVERSE WITH CONFIDENCE™

- KOREAN MADE MONITOR
- REAR VIEW CAMERA IS COMPLETELY WEATHER PROOF WITH AN IP68 RATING,
- 6 INFRA-RED LIGHTS FOR AMAZING VISION AT NIGHT
- KOREAN MADE 2.1MM LENS WITH A VIEWING ANGLE OF 130° AND 480 TV LINES
- CRYSTAL CLEAR 7" DIGITAL TFT LCD COLOR MONITOR WITH MIRROR IMAGE CAPABILITY



## MONITOR

TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 WIDE SCREEN
DISPLAY BRIGHTNESS	400CD/M <sup>2</sup>
VIEWING ANGLE	TOP: 50° BOTTOM: 70° L/R: 70°
VIDEO INPUT	4 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 11V - 32V (+/-10%)
AUDIO OUTPUT	1W MONO SPEAKER
OPERATING TEMPERATURE	-20 °C ~ +60 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	181MM (L) X 121MM (H) X 24MM (D)
WEIGHT	450G
IMPACT RATING	10G
SYNC SYSTEM	INTERNAL

## CAMERA

CAMERA	1/3" SONY SUPER HAD COLOR CCD
PICTURE ELEMENTS	NTSC: 270,000 / PAL: 320,000
IMAGE SENSOR	480 TV LINES
VIEW ANGLE	130°
AUDIO INPUT	HIGH SENSITIVE C-MIC
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA - RED DISTANCE	30 FEET (6 INFRA - RED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V - 30V (+/- 10%)
S/N RATIO	MORE THAN 48DB
VIDEO OUTPUT	1VP - P, 75 Ω
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-30 °C ~ +70 °C / RH 95% MAX
STORAGE TEMPERATURE	-40 °C ~ +80 °C / RH 95% MAX
WEIGHT	265G