

# BACKUP CAMERA SYSTEM FOR NISSAN NV VANS

REAR VIEW  
**SAFETY**  
A Safe Fleet Brand

RVS - 912619-NM



This Nissan NV Backup Camera System is complete with a crystal clear 7" COLOR TFT LCD Digital Mirror Monitor with a 16:9 wide screen and distance grid lines, a 130° angle backup camera with night vision and all the wires, connectors and mounts you will need. The Nissan NV Rear View Backup Camera is completely weatherproof with an IP68 rating, strong and reliable, shock resistant, with a 10G vibration rating (highest in the industry). The entire system comes with a full year warranty. This Nissan NV Backup Camera works on 1500, 2500 and 3500 series Nissan NV Bodies 2012 -2016.

Note: Not compatible with the NV200 vehicle)

# BACKUP CAMERA SYSTEM FOR NISSAN NV VANS RVS - 912619-NM



- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 7" TFT LCD DIGITAL COLOR MONITOR
- COMES WITH OPTIONAL GRID LINES AND AN IN-BUILT SPEAKER
- MT9V139 COLOR CAMERA WITH A 130° VIEWING ANGLE
- ALL FUNCTIONS CONTROLLED WITH THE ON-SCREEN TOUCH BUTTONS OR REMOTE



## MONITOR

MONITOR TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m <sup>2</sup>
VIEWING ANGLE	90° MIN
VIDEO INPUT	3 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-10°C ~ +65° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	9" (L) X 4.5" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	INTERNAL

## CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES, PAL:720 (H) X 576 (V), NTSC: 720 (H) X 480 (V)
LENS	2.1MM
VIEW ANGLE	130°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.3 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-30°C ~ +50°C / RH 95% MAX
STORAGE TEMPERATURE	-30°C ~ +60°C / RH 95% MAX