

BACKUP CAMERA SYSTEM FOR GMC SAVANA VANS

RVS-913S619-NM

REAR VIEW
SAFETY
A Safe Fleet Brand



This GMC Savana Van backup camera system is complete with a crystal clear DIGITAL 7" TFT LCD color monitor with distance grid lines, a power harness, 130° MT9V139 rear backup camera with night vision and all the wires, connectors and mounts you will need. The GMC Savana Rear View Backup Camera is completely weatherproof with an IP68 rating, strong and reliable, shock resistant, with a 10G vibration rating (highest in the industry), and the system comes with a full year warranty. Works on GMC Savana and Chevy Express models from 2003 and onward.

BACKUP CAMERA SYSTEM FOR GMC SAVANA VANS RVS-913S619-NM

**REAR VIEW
SAFETY**
A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 7" TFT LCD DIGITAL COLOR MONITOR
- COMES WITH OPTIONAL GRID LINES AND A BUILT - IN SPEAKER
- MT9V139 COLOR CAMERA WITH A 130° VIEWING ANGLE
- ALL FUNCTIONS CONTROLLED WITH THE ON - SCREEN TOUCH BUTTONS OR REMOTE



MONITOR

TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	90°
VIDEO INPUT	3 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-10°C ~ +65° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	9" (L) X 4.5" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	600 TV LINES, PAL: 720 (H) X 576 (V) NTSC: 720 (H) X 480 (V)
LENS	2.1MM
VIEW ANGLE	130°
WATERPROOF RATING	IP68
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
IMPACT RATING	10G
OPERATING TEMPERATURE	-30°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-30°C ~ +60°C / RH 95% MAX