

BACKUP CAMERA SYSTEM THREE CAMERA SETUP RVS - 770615-NM

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



This three camera system is complete with a crystal clear 7" LED Digital Panel COLOR monitor with distance grid lines and mirror image capability, a 3 input power harness, three (3) 130° CCD cameras with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry), it also comes with a full year warranty. System can be upgraded to the Quad View Monitor where multiple cameras can be viewed simultaneously.

BACKUP CAMERA SYSTEM

THREE CAMERA SETUP

RVS - 770615-NM



- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" LED DIGITAL PANEL MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM COLOR CCD CAMERAS WITH A 130° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

TYPE	LED DIGITAL PANEL
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT/CONTRAST	16:09 / 500:01:00
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U:50° D:60° L/R:70°
VIDEO INPUT	3 CHANNEL CVBS
VIDEO SOURCE	1VP - P 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
AUDIO OUTPUT	0.5W SPEAKER
OPERATING TEMPERATURE	-20°C ~ +70° C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
ACTIVE AREA	154.08 (H) X 85.92 (V)
SYNC SYSTEM	INTERNAL

CAMERA

NOTE: DETAILS MAY CHANGE BASED ON ITEM CONFIGURATION

CAMERA	1/3" SHARP COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 811 (H) X 582 (V)
	NTSC: 811 (H) X 507 (V)
	F=2.5MM
LENS	130°
VIEW ANGLE	IP69K
WATERPROOF RATING	INTERNAL SYNCHRONIZATION
SYNC SYSTEM	50 FEET (18 INFRARED)
INFRA-RED DISTANCE	0 LUX (IR ON)
USABLE ILLUMINATION	DC 9V-32V
POWER SOURCE	MORE THAN 48DB
S/N RATIO	1/50, 160-1/100,000SEC
ELECTRONIC IRIS	1VP - P 75 Ω
VIDEO OUTPUT	ACDS AUTOMATIC CONTROL
IR SWITCH CONTROL	20G / 100G
VIBRATION AND SHOCK RATING	-40°C ~ +70°C / RH 95% MAX
OPERATING TEMPERATURE	-40°C ~ +85°C / RH 95% MAX
STORAGE TEMPERATURE	22OZ
NET WEIGHT	