

BACKUP CAMERA SYSTEM WITH SIDE CAMERA

RVS-7706135-NM

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



This 2 camera system is complete with a crystal clear 7" LED Digital Panel color monitor with mirror image capability, a 3 port power harness, two (2) CCD cameras with 130° and 120° viewing angle respectively, 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry), and comes with a full year warranty.

BACKUP CAMERA SYSTEM WITH SIDE CAMERA RVS-7706135-NM



- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" LED DIGITAL PANEL COLOR MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM CCD COLOR BACKUP CAMERA WITH A 130° VIEWING ANGLE
- 2.1 MM CCD COLOR SIDE CAMERAS WITH A 120° VIEWING ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

PANEL SIZE	7" LED DIGITAL PANEL
DOT RESOLUTION	800 X 3 (RGB) X 480
SCREEN MODE	16:9
CONTRAST RATIO	500:1
DISPLAY BRIGHTNESS	400 CD/m ²
FIELD OF VIEW	U-50° D-60° L/R-70°
CAMERA INPUT	3 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-20°C ~ +70°C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D)
WEIGHT	400G
VIBRATION RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
SYNC SYSTEM	INTERNAL

RVS-770 CAMERA

SENSOR	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES, PAL: 752 (H) X 582 (V), NTSC: 811 (H) X 507 (V)
LENS	2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 1/60-1/100,000 SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G/100G
OPERATING TEMPERATURE	-40°C ~ 70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ 85°C / RH 95% MAX
NET WEIGHT	22 OZ

RVS-775 CAMERA

SENSOR	1/4" SHARP® COLOR CCD
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	420 TV LINES, PAL: 500 (H) X 582 (V), NTSC: 510 (H) X 492 (V)
LENS	2.1MM
VIEW ANGLE	120°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	30 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000 SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G/100G
OPERATING TEMPERATURE	-40°C ~ +80°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +60°C / RH 95% MAX