

COMMERCIAL GRADE HD BACKUP CAMERA SYSTEM



This is the system you've been waiting for. The RVS-770613-HD is the HD version of our popular Backup Camera System that put us on the map all those years ago. The system is complete with a 7" HD monitor and an HD waterproof backup camera. The backup camera has an ultra-wide 130° viewing angle, and 18 Infra-red illuminators enable you to see everything behind you, even in total darkness. This unique system is truly the future of safety technology.

Note: Minor details may change based on item configuration

HD BACKUP CAMERA SYSTEM



A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" HD DIGITAL TFT LCD COLOR MONITOR WITH MIRROR IMAGE CAPABILITY
- 4 CHANNELS ALLOWING YOU TO CONNECT ADDITIONAL CAMERAS
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

MONITOR TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	1024 X 600 PIXELS (RGB)
CAMERA INPUT & TRIGGERS	4 CHANNELS
VIDEO DISPLAY SYSTEM	NTSC / PAL AUTO
BRIGHTNESS	500 CD/M ²
DISPLAY ASPECT RATIO	16:9 WIDE SCREEN
FIELD OF VIEW	TOP 85° / BOTTOM 85° / LEFT 85° / RIGHT 85°
CAMERA INPUT	4VCH, TVI 720P
DIMMER	CDS SENSOR (AUTOMATIC) OR MANUAL ADJUSTMENT
AUDIO OUTPUT	0.5 W SPEAKER
IMPACT OUTPUT	6G
STORAGE TEMPERATURE	-20°C ~ +70°C
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	INTERNAL
DIMENSION	5.25" (H) X 7" (L) X 1" (D)

CAMERA

HDRI	WDR FUNCTION (WIDE DYNAMIC RANGE)
CDS SENSOR	LED AUTO ON / OFF
WATERPROOF RATING	IP69K
INFRA-RED ILLUMINATORS	18
AUDIO SOURCE	BUILT-IN MICROPHONE
PIXEL RATIO	1288 X 720
VIDEO SIGNAL SYSTEM	TVI
S/N RATIO	≥50DB (AGC OFF)
MINIMUM ILLUMINATION	0 LUX (WITH IR LED)
LENS	F2.5
VIEWING ANGLE	130°
POWER INPUT RANGE	MDC12V+/10%
POWER CONSUMPTION	IR ON MAX (180MA), IR OFF MAX (90MA)
OPERATING TEMPERATURE	-40°C ~ +70°C
STORAGE TEMPERATURE	-40°C ~ +70°C
AMBIENT HUMIDITY	RH 85% MAX

Note: Minor details may change based on item configuration