



**Technical requirements:**

1. Welding and assembly must ensure accurate ranking.
2. The cutting length are 8 meters, 4 meters, and 0.3 meters, respectively.
3. O-ring and waterproof cover is provided at the aviation head.

ALL MASTER DRAWINGS, WHICH REPRESENT THE CURRENT REVISION, ARE STORED ELECTRONICALLY, AND ALL SUBSEQUENT COPIES ARE CONSIDERED UNCONTROLLED.

THIS DRAWING AND THE DESIGN SHOWN THEREIN IS THE PROPERTY OF REAR VIEW SAFETY, INC. AND USE OR COPIES THEREOF CANNOT BE MADE WITHOUT WRITTEN CONSENT.

Rev	Revision	By	Ck.By	Auth.	Date
0					
1					



A Safe Fleet Brand

Rear View Safety, Inc.  
1797 Atlantic Ave  
Brooklyn, N.Y. 11233

TOLERANCES  
UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE  
IN MILLIMETERS  
0 DECIMALS  $\pm$  1.5mm  
0.0 DECIMALS  $\pm$  1mm  
ANGULAR TOLERANCES  $\pm$  1v



ITEM N°:	RVS-213
DESCRIPTION	QUICK CONNECT KIT
DWG NO	12-366-2
DWG SIZE	
DATE	