

# Backup Camera



Flush Mount Backup Camera, FHD, 4P Male

## CA-659M1

FMVSS 111 regulates a necessary view behind a vehicle. The rule impacts vehicles with a gross vehicle weight rating (GVWR) of under 10,000 pounds, with phase-in effective by May 2017 and full compliance required by May 1st, 2018. The backup camera is about 1.43" in diameter and mounts flush in the back of a vehicle. Simply drill a 1.02" hole at the rear of your vehicle with the included hole for a clean install. This camera will make your vehicle compliant with FMVSS 111. The CA-659M1 has 700 TV Lines and a 170° viewing angle.



### FMVSS 111

Depending on installation location, this camera makes your vehicle FMVSS 111 compliant.

### HIGH RESOLUTION

The CA-659M1 provides a high resolution of 700 TV Lines.

### WIDE VIEWING ANGLE

Mounts flush against vehicle and provides a 170° Viewing angle.

#### Camera Specs

Sensor	1/3 PC1099
Active Array	960 X 480
Viewing Angle	170°
Waterproof Rating	IP68
Resolution	700 TV Lines
Minimum Light	0.5 Lux
AGC	Auto
BLC	Auto
S/N Ratio	More than 48dB
Video Output	1Vp-p 75Ω
Voltage	DC12V
Operating Temperature	-40 ~ +70 °C



Rear View Safety, 1797 Atlantic Ave., Brooklyn NY 11233  
800.764.1028 sales@rearviewsafety.com  
www.rearviewsafety.com

844.258.8178  
safefleet.net

SAFE  FLEET  
Driving Safety Forward™