

120° HEATED CAMERA WITH 30 INFRA-RED ILLUMINATORS

RVS-812N



SPECIFICATIONS



IMAGE DEVICE	1/3" SONY® SUPER HAD CCD
TV SYSTEM	PAL / NTSC
TOTAL NUMBER OF PIXELS	PAL: 537 (H) × 597 (V) / NTSC: 537 (H) × 505 (V)
EFFECTIVE PIXELS	PAL: 500 (H) × 582 (V) / NTSC: 510 (H) × 492 (V)
SENSING AREA	4.9 MM (H) × 3.7 MM (V)
SYNC. SYSTEM	INTERNAL
RESOLUTION	700 TV LINES
MINIMUM ILLUMINATION	0 LUX (WITH IR)
MICROPHONE	YES
VIDEO OUTPUT	COMPOSITE SIGNAL (1.0 VP-P, 75 Ω)
GAMMA CORRECTION	0.45
AGC	ON
S/N RATIO	BETTER THAN 48 DB
WHITE BALANCE	AUTO
ELECTRONIC SHUTTER	1/50-1/100,000 SEC. / 1/60-1/100,000 SEC.
BLC	AUTO
CURRENT CONSUMPTION	MAX. 300 MA
POWER SUPPLY	DC 12 V
ANTI-VIBRATION	5.9 G
OPERATING TEMPERATURE	-45°C~70°C, RH 95% MAX.
STORAGE TEMPERATURE	-45°C~80°C, RH 95% MAX.
LENS	3.6 MM OPTIONAL
LENS ANGLE	120°

RVS

A Safe Fleet Brand