

Backup Camera System with Replacement Mirror Monitor and Quick Connect/Disconnect Kit

RVS-770718-213

REAR VIEW
SAFETY
A Safe Fleet Brand



This backup camera system is perfect for the fifth wheel application. The system is complete with a crystal clear 4.3" TFT LCD Digital mirror monitor with mirror image capability and distance grid lines, a 2 channel power harness with automatic system switch, one 130° CCD camera with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. See item options on the right to choose either a replacement or clip-on mirror monitor. The quick connect/disconnect cable is 66' to camera, 26' to monitor with a 12' pigtail.

The system is strong and reliable with a completely waterproof camera (IP69k) that boasts a 20G vibration and 100G impact rating (highest in the industry) and comes with a full year warranty.

Backup Camera System with Replacement Mirror Monitor and Quick Connect/Disconnect Kit



RVS-770718-213

- Trailer Tow Quick Connect Kit - for Trucks and Trailers
- 4.3" TFT-LCD Mirror Monitor
- Acts as a Mirror as well as a Monitor
- Completely Waterproof Backup Camera with 18 Infra-red Lights



MONITOR SPECIFICATIONS

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	400
VIEWING ANGLE	U&D: 100° , L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
VIBRATION RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA SPECIFICATIONS

CAMERA	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V) NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX