

# 130° CAMERA WITH 18 INFRA-RED ILLUMINATORS (RCA CONNECTORS)

## RVS-771



## SPECIFICATIONS

CAMERA  
PICTURE ELEMENTS  
GAMMA CORRECTION  
IMAGE SENSOR  
  
LENS  
VIEW ANGLE  
SYNC SYSTEM  
INFRA-RED DISTANCE  
USABLE ILLUMINATION  
POWER SOURCE  
S/N RATIO  
ELECTRONIC IRIS  
VIDEO OUTPUT  
IR SWITCH CONTROL  
WATERPROOF RATING  
VIBRATION AND SHOCK RATING  
OPERATING TEMPERATURE  
STORAGE TEMPERATURE

1/3 SHARP® COLOR CCD  
410,000 PIXELS  
R=0.45 TO 1.0  
620 TV LINES PAL:752(H)\*582(V),  
NTSC:811(H)\*507(V)  
2.5MM  
130°  
INTERNAL SYNCHRONIZATION  
50 FEET (18 INFRARED IR)  
0 LUX (IR ON)  
DC 12V  
MORE THAN 48DB  
1/50, 1/60-1/100,000SEC  
1VPP 75 Ω  
CDS AUTOMATIC CONTROL  
IP69K  
20G / 100G  
-40°C ~ 70°C / RH 95% MAX  
-40°C ~ 85°C / RH 95% MAX

# RVS

A Safe Fleet Brand